

## Maxol Supersynth 5W/30

### Description:

A universal, synthetic fuel economy motor oil developed according to the most recent technology and based on specially selected base oils with a high natural viscosity index. With the addition of a well-balanced choice of advanced additives the following properties are obtained:

- Lower fuel consumption
- High and very stable viscosity index
- High resistance against shearing
- Fast cold start
- Safe lubrication film at very high temperatures
- Reduced formation of combustion ashes
- Very good detergency and dispersion
- Very strong protection against wear, corrosion and foaming

### Application:

This universal, fuel saving synthetic motor oil, is specially developed for passenger car unit injector diesel engines. Moreover this lubricant is very suitable for use in petrol and diesel engines, with or without turbo-charging. This product meets the requirements of several OEM's and thus has a wide application.

### Performance Level:

ACEA C2, C3
API SN
MB 229.51/229.52
VW 505.01
Dexos 2
BMW Longlife-04

### Typical Characteristics:

Density at 15 °C, kg/l	0.848
Viscosity -30 °C, mPa.s	6400
Viscosity 40 °C, mm <sup>2</sup> /s	74.40
Viscosity 100 °C, mm <sup>2</sup> /s	12,30
Viscosity Index	163
Flash Point COC, °C	242
Pour Point, °C	-36
Total Base Number, mgKOH/g	7.8
Sulphate Ash, %	0,77

### Important:

Always observe the manufacturers specifications when selecting products.  
Maxol Lubricants reserve the right to change this product specification without notice.

### Maxol Lubricants Ltd.

Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.  
Tel: +353 (0) 1 806 0300 Web: [www.maxol.ie](http://www.maxol.ie)

