

Tor Specialsynth FE 0W20

Description:

A modern, synthetic, fuel economy motor oil based on special selected synthetic base oils with a high viscosity index and a well balanced choice of advanced additives to obtain the following properties:

- a lower fuel consumption
- a high and very stable viscosity index
- a high resistance against shearing
- a very fast cold start
- a very strong resistance against oxidation
- a safe lubrication film at very high temperatures
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

Application:

A modern fuel economy, special composed synthetic motor oil suitable for use in petrol and diesel engines of passenger cars and delivery vans. This oil is fully backward compatible with BMW Longlife - 14 FE+

Performance Level :

ACEA C5, C6
API SP Resource Conserving
ILSAC GF - 6A
BMW Longlife-17 FE+
Ford WSS-M2C947-B1/WSS-M2C962-A1
Jaguar Land Rover STJLR.03.5006
Fiat 9.55535-GSX
MB 229.71/229.72
Opel OV0401547
Chrysler MS-GSX

Typical Characteristics:

Density at 15 °C, kg/l	0,845
Viscosity -35 °C, mPa.s	5260
Viscosity 40 °C, mm ² /s	41,60
Viscosity 100 °C, mm ² /s	8,30
Viscosity Index	179
Flash Point, COC °C	222
Pour Point, °C	-51
Total Base Number, mgKOH/g	7,8
Sulphate Ash, %	0,77

Important:

Always observe the manufacturers specifications when selecting products.
Maxol Lubricants reserve the right to change this product specification without notice.

Maxol Lubricants Ltd.

Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.
Tel: +353 (0) 1 806 0300 Web: www.maxol.ie

