

Maxol Autotrans

Description:

A very high graded automatic transmission fluid formulated with solvent refined base oils and a number of selected additives to obtain the following properties:

- High and stable viscosity index
- Very low pour point
- Very good stability against oxidation
- Positive activity against wear, corrosion and foam
- Specific friction properties
- Perfect compatibility with seals and non-ferro metals
- Red coloured

Application:

This fluid may be used for automatic gearboxes, power steering units, torque converters and other equipment, for which an ATF Dexron IID fluid is required.

Performance Level:

GM Dexron IID
MB 236.6/236.7
MAN 339 Typ Z1/V1
ZF TE-ML 09/11A/14A
Allison C4
Ford SQM-2C9010-A
Voith 55.6335 (G607)
Cat TO-2
Renk
Ford M2C138-CJ/166-H
Ford Mercon

Typical Characteristics:

Density at 15 °C, kg/l	0,872
Viscosity 40 °C, mm ² /s	43,20
Viscosity 100 °C, mm ² /s	8,25
Viscosity Index	168
Flash Point COC, °C	198
Pour Point, °C	-45
Total Base Number, mgKOH/g	2,6
Sulphate Ash, %	0,18

Important:

Always observe the manufacturers specifications when selecting products.
Maxol Lubricants reserve the right to change this product specification without notice.

Maxol Lubricants Ltd.

Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.
Tel: +353 (0) 1 806 0300 Web: www.maxol.ie

