

Maxol ATF III H

Description:

Maxol ATF III H is a very high graded automatic transmission fluid formulated with solvent-refined base oils and a number of selected additives.

- High and stable viscosity index
- Very low pour point
- Very good stability against oxidation
- Positive activity against wear, corrosion and foam
- Specific friction properties
- Perfect compatibility with seals and non-ferro metals
- Red coloured

Application:

This fluid may be used for automatic gearboxes, power steering units, torque converters and other equipment, for which an ATF Dexron IIIH fluid is required.

Performance Level:

Dexron IIIH
Ford Mercon
MAN 339 Typ Z1/V1
Allison C4/TES-389
ZF TE-ML 09B/11B/14A
Voith 55.6335
MB 236.1/236.5
Volvo 97341
Cat TO-2

Typical Characteristics:

Density at 15 °C, kg/l	0.853
Viscosity 40 °C, mm ² /s	34.40
Viscosity 100 °C, mm ² /s	7.28
Viscosity Index	184
Flash Point COC, °C	220
Pour Point, °C	-48
Total Base Number, mgKOH/g	2.4

Important:

Always observe the manufacturers specifications when selecting products.
Maxol Lubricants reserve the right to change this product specification without notice.

Maxol Lubricants Ltd.

Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.
Tel: +353 (0) 1 806 0300 Web: www.maxol.ie

