

Maxol ATV Oil 10W/40

Description:

A new generation semi-synthetic engine oil for four-stroke motorcycles formulated with high quality mineral and synthetic base oils combined with special developed balanced additives to achieve the following properties:

- High and stable viscosity index
- Good cold start properties
- Optimal friction characteristics
- Very strong protection against wear, corrosion and foaming
- Very good detergency and dispersion

Application:

This oil is special developed for the lubrication of four-stroke motorcycles, so that sliding, sticking and/or rough changing of the clutch-plates no longer occurs. This oil is developed and tested in co-operation with the most important motorcycle producers and has its performance demonstrated in the field.

Performance Level:

Meets the requirements of
JASO MA2

Typical Characteristics:

Density at 15 °C, kg/l	0,871
Viscosity -25 °C, mPa.s	5560
Viscosity 40 °C, mm ² /s	101,00
Viscosity 100 °C, mm ² /s	15,00
Viscosity Index	156
Flash Point COC, °C	210
Pour Point, °C	-30
Total Base Number, mgKOH/g	7,7
Sulphate Ash, %	0,94

Important:

Always observe the manufacturers specifications when selecting products.
Maxol Lubricants reserve the right to change this product specification without notice.

Maxol Lubricants Ltd.

Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.
Tel: +353 (0) 1 806 0300 Web: www.maxol.ie

