

Maxol Hydraulic D 32

Description:

A high grade detergent hydraulic oil based on carefully selected solvent refined base oils with a natural viscosity index, under addition of additives to obtain the following properties:

- very good wear-preventing properties
- a very good activity against corrosion
- an excellent stability against oxidation
- very good detergency and dispersion
- very good deaerating and foam suppressing properties
- good compatibility with seals and gaskets made from synthetic material
- ability to absorb small amounts of water
- a low pour point

Application:

This detergent hydraulic oil is a tailor made quality for heavy duty hydraulic systems as well as for gear drives and bearings under light service conditions. This detergent hydraulic oil can also be used as circulating lubricant (not in turbines) and for the general lubrication of machinery. This fluid is **not** compatible in systems, containing parts or equipment with a silver lining.

Performance Level:

DIN 51524-2 HLPD

Typical Characteristics:

Density at 15 °C, kg/l	0,853
Viscosity 40 °C, mm ² /s	32,00
Viscosity 100 °C, mm ² /s	5,35
Viscosity Index	98
Flash Point COC, °C	205
Pour Point, °C	-32
Acid number, mgKOH/g	4,80

Important:

Always observe the manufacturers specifications when selecting products.
Maxol Lubricants reserve the right to change this product specification without notice.

Maxol Lubricants Ltd.

Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.
Tel: +353 (0) 1 806 0300 Web: www.maxol.ie

