

## Maxol 0W/30 FS LL VW

### Description:

Maxol 0W/30 FS LL VW is a fuel economy, fully synthetic motor oil produced with advanced new technology additives.

- Lower fuel consumption
- Very high viscosity index
- High resistance against shearing
- Fast cold start
- Safe lubrication film at high temperatures
- Very good detergency and dispersion
- Very strong protection against wear, corrosion and foaming

### Application:

This fuel saving, fully synthetic motor oil is specially developed for use in petrol- and diesel engines of VW passenger cars and delivery vans with extended oil drain intervals. This oil is also applicable in those engines, where the specifications as stated below are requested.

**This oil is not applicable in those cases where a VW-Norm 503.01 is requested.**

### Performance Level:

ACEA A1/B1, A5/B5
VW 503.00/506.00/506.01

### Typical Characteristics:

Density at 15 °C, kg/l	0.857
Viscosity -30 °C, mm <sup>2</sup> /s	3100
Viscosity 40 °C, mm <sup>2</sup> /s	55.30
Viscosity 100 °C, mm <sup>2</sup> /s	10.10
Viscosity Index	174
Flash Point COC, °C	226
Pour Point, °C	-50
Total Base Number, mgKOH/g	10.2
Sulphate Ash, %	1.28

### Important:

Always observe the manufacturers specifications when selecting products. Maxol Lubricants reserve the right to change this product specification without notice.

### Maxol Lubricants Ltd.

Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.  
Tel: +353 (0) 1 806 0300 Web: [www.maxol.ie](http://www.maxol.ie)

