

## Maxol Torque FLD 4-50

### Description:

Maxol Torque FLD 4-50 is a special oil for hydraulic- and transmission equipment formulated with solvent refined base oils and selected additives.

- Low pour point
- Very good stability against oxidation
- Very good anti-wear properties, that gives a longer duration of the final drive
- Specific friction-properties, which grants an optimum use of the power shift transmissions
- Applicable in systems with "wet" brakes
- Excellent corrosion and foaming preventive properties

### Application:

This oil is special developed for the lubrication of power shift transmissions, differentials, final drives and hydraulic equipment of earth-moving equipment, for which a Caterpillar TO-4 or Allison C4 fluid is required.

This oil cannot be used in engines.

### Performance Level:

Allison C4
Cat TO-4/TO-2

### Typical Characteristics:

Density at 15 °C, kg/l	0.889
Viscosity 40 °C, mm <sup>2</sup> /s	199.50
Viscosity 100 °C, mm <sup>2</sup> /s	17.50
Viscosity Index	94
Flash Point COC, °C	240
Pour Point, °C	-12
Total Base Number, mgKOH/g	7.6
Sulphate Ash, %	1.02

### Important:

Always observe the manufacturers specifications when selecting products.  
Maxol Lubricants reserve the right to change this product specification without notice.

### Maxol Lubricants Ltd.

Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.  
Tel: +353 (0) 1 806 0300 Web: [www.maxol.ie](http://www.maxol.ie)

