

## Tor Specialsynth P 5W30

### Description:

A synthetic, fuel economy, universal motor oil, developed according the most recent technology, based on specially selected synthetic base oils to which advanced additives are added to obtain the following properties: - a lower fuel consumption - suitable for modern catalysts - a fast cold start - a safe lubrication film at high temperatures - extended oil drain intervals - a very good detergency and dispersion - a very strong protection against wear, corrosion and foaming

**Application:** This universal, synthetic, fuel economy, "mid SAPS" motor oil is recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans with extended oil drain intervals. Due to its low SAPS content this product can be applied in vehicles with modern three way catalysts and diesel particle filters.

### Performance Level:

ACEA C2, A5/B5
PSA B71 2290
API SN

### Typical Characteristics:

Density at 15 °C, kg/l	0,852
Viscosity -30 °C, mPa.s	5650
Viscosity 40 °C, mm <sup>2</sup> /s	58,60
Viscosity 100 °C, mm <sup>2</sup> /s	10,40
Viscosity Index	168
Flash Point, COC°C	224
Pour Point, °C	-36
Total Base Number, mgKOH/g	8,0
Sulphate Ash, %	0,80

### Important:

Always observe the manufacturers specifications when selecting products. Maxol Lubricants reserve the right to change this product specification without notice.

### Maxol Lubricants Ltd.

Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.  
Tel: +353 (0) 1 806 0300 Web: [www.maxol.ie](http://www.maxol.ie)

